

## METHOD STATEMENT

### TPS THIN BED ADHESIVES (PREMIUM)



#### 1. INTRODUCTION

TPS Thin Bed Adhesive (Premium) is a polymer-modified, cement-based adhesive designed for fixing large ceramic tiles, homogeneous tiles, granite, marble stone tiles, and similar finishes on walls and floors. This adhesive is classified as C2TES1 according to EN 12004 / ISO 13007,

#### 2. SUBSTRATE PREPARATION & INSPECTION

- a) Ensure all surfaces are structurally sound, level, clean, and free from dust, oil, grease, curing compounds, paint flakes, laitance, and any foreign matter that may impair adhesion.
- b) Concrete walls/floors must be cured for a minimum of 28 days before tiling.
- c) Cement renders and screeds must be cured for at least 7 days, finished to a semi-smooth surface with a wood float, and checked for sound adhesion. Cracks must be repaired before tiling.
- d) Painted surfaces must be mechanically roughened (wire brush or grinding) to expose a sound substrate. Loose or flaking paint must be removed.
- e) Background tolerances must comply with tiling standards. When checked with a 2m straightedge, the deviation must not exceed 3 mm. Local correction (up to 6 mm) may be carried out using TPS Thin Bed Adhesive.



### 3. MATERIAL PREPARATION

- One (1) bag of TPS Tile Adhesive Premium = 40 kg.

- Water required: 8 litres (20% by weight of cement).

*\*\*Mixing water must be potable, free from salts and organic impurities.*

- Coverage:

a) AAC Block - 19m for 100mm block

b) 2' x 2' Tile: approximately 6 pieces (varies with trowel thickness and wall leveling)

Recommended tile sizes:

– Wall tiles: up to 1200mm × 1200 mm

– Floor tiles: up to 1200mm × 1200 mm

*\*\*For larger tiles that are above 600mm x 600mm, vacuum suction cup hook is strongly recommended during installation for safety purposes.*



### 4. MIXING PROCEDURE

a) Pour the measured clean water into a suitable mixing container.

b) Gradually add the powder while mixing continuously with a slow-speed drill mixer (400–600 rpm).

c) Mix for 3–5 minutes until a smooth, homogenous, lump-free paste is achieved.

d) Allow the mixture to stand (slake) for 3–5 minutes. Re-mix before application.

e) Do not add extra water after mixing.

*\*\*Pot life: Up to 1 hour after mixing.*

## 5. APPLICATION



- a) Spread adhesive onto the prepared substrate using a trowel, then comb through with a notched trowel of appropriate size (e.g., 6 mm × 6 mm for tiles ≤ 300 mm × 300 mm).
- b) Do not spot-fix tiles. If tile backs are dusty, clean with a damp cloth.
- c) Apply only as much adhesive as can be installed within the product's open time (~20 minutes). Do not allow the adhesive surface to skin before tiling. Total thickness of the adhesive should not exceed 10mm after pressed/hammered/levelling.
- d) After spreading the adhesive, press/hammer the tile firmly with rubber hammer into place with a slight sliding/twisting motion to achieve maximum coverage.
- e) For tiles ≥ 300 mm × 300 mm, or with deep ribs/lugs, back-butter the tile with 4-5 mm adhesive to ensure full bedding and eliminate voids.
- f) Periodically remove a tile during fixing to check proper adhesive contact coverage (minimum 80% internal, 95% external, as per ISO 13007).

## 6. CURING & PROTECTION

- a) Tiles must not be exposed to running water or rain for at least 24 hours after installation.
- b) Grouting can commence after 24 hours.
- c) Light foot traffic is permitted after 4 days.
- d) Heavy foot traffic and loading are permitted only after 14 days.
- e) Protect tiled areas with boards or sheets against impact, staining, or contamination during curing.
- f) Avoid application under direct sunlight, rain, or strong wind.
- g) Recommended substrate temperature: 5°C – 35°C.

## 7. QUALITY ASSURANCE & SAFETY

- Conforms to ISO 13007 / BS EN 12004 requirements for cementitious adhesives.
- Ensure mixing water is clean and potable.
- Wear gloves, goggles, and dust mask. Avoid inhalation of dust and contact with skin.
- First aid: In case of contact with skin or eyes, rinse immediately with clean water and seek medical advice if irritation persists.



## 8. DISCLAIMER

The information provided herein is based on our best knowledge and is intended as a general guide for the proper use of TPS Tile Adhesive (Premium). Conditions of use are beyond the manufacturer's control, and no warranty is expressed or implied. It is the responsibility of the applicator/contractor to determine the suitability of the product for the intended application.

Last Revision: [13/3/2025]